

## 7.4kW Single-Phase Basic PDU, 230V Outlets (4-C19), IEC309 32A Blue, 12ft Cord, 1U Rack-Mount

MODEL NUMBER: PDUH32HV19



### Highlights

- Basic single phase 32A 230V PDU
- 1U horizontal rackmount installation
- Blue IEC309 32A (2P+E) input; 12 ft. / 3.6m line cord
- 4 C19 outlets
- Reversible housing; 5.2 in. / 13.2 cm depth

### Package Includes

- PDUH32HV19 Power Strip
- Warranty information
- Instruction manual

### Description

Tripp Lite Basic Power Distribution Units / PDU systems offer reliable rackmount power distribution. Supplies equipment with continuous power from any protected UPS, generator or mains input power source. High quality design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

### Features

- 32A single phase 230V Basic Power Distribution Unit / PDU
- Attached Blue IEC-309 32A (2P+E) 230V input plug with 12 ft. / 3.6m line cord
- 1U horizontal rackmount format installs in one rack space
- 4 C19 outlets
- Mounting flanges are reversible front or rear facing installation
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats

## Specifications

OVERVIEW	
PDU Type	Basic
OUTPUT	
Output Capacity Details	7.4kW (230V), 7kW (220V), 7.7kW (240V); 32A maximum total output, 20A max per breakered load bank, 16A max per C19 outlet
Frequency Compatibility	50 / 60 Hz
Output Receptacles	(4) C19
Output Nominal Voltage	200-240V nominal, single phase



Overload Protection	Two 20A circuit breakers protect 2 outlets each
Outlet Type	IEC-C19
Individual Outlet Switching	No
<b>INPUT</b>	
PDU Input Voltage	200; 208; 220; 230; 240
Recommended Electrical Service	32A 230V
Maximum Input Amps	32
PDU Plug Type	IEC-309 32A BLUE (2P+E)
Input Cord Length (ft.)	12
Input Cord Length (m)	3.6
Input Phase	Single-Phase
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
Switches	n/a
<b>PHYSICAL</b>	
Shipping Dimensions (hwd / in.)	3 x 20.25 x 11.25
Shipping Dimensions (hwd / cm)	7.6 x 51.4 x 28.6
Shipping Weight (lbs.)	7.07
Shipping Weight (kg)	3.21
Unit Dimensions (hwd / in.)	1.75 x 17.5 x 5.2
Unit Dimensions (hwd / cm)	4.5 x 44.5 x 9.5
Unit Weight (lbs.)	6.32
Unit Weight (kg)	2.87
Material of Construction	Metal
Form Factors Supported	1U rackmount, 0U vertical mount, wallmount and under-counter
PDU Form Factor	Horizontal (1U, 2U, etc)
<b>ENVIRONMENTAL</b>	
Storage Temperature Range	-15 to 50C (5 to 122F)
Relative Humidity	5 to 95% non-condensing
Operating Elevation (ft.)	0-10,000
Operating Elevation (m)	0-3000
<b>SPECIAL FEATURES</b>	



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

TVSS Grounding	Rear grounding lug
<b>CERTIFICATIONS</b>	
Certifications	Tested to UL60950-1, CE (EN 60950-1), CE Class A, RoHS
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>