



# 2-Port Mini DisplayPort to VGA Hub, DP1.2, TAA

## MODEL NUMBER: B155-002-VGA











Converts and splits a Mini DisplayPort video signal for display on two VGA monitors, projectors or televisions at the same time. Ideal for offices, conference rooms, retail settings, trade shows and classrooms.

#### Description

The B155-002-VGA 2-Port Mini DisplayPort to VGA Splitter converts and splits a Mini DisplayPort video signal for display on two VGA-enabled monitors, projectors or televisions at the same time. Ideal for offices, conference rooms, retail settings, trade shows and classrooms, this compact splitter features a built-in Mini DisplayPort cable that connects to the source. It lets you use your existing VGA displays instead of buying new Mini DisplayPort monitors or docking stations.

The B155-002-VGA supports video resolutions up to 1080p @ 60 Hz (1920 x 1080), as well as HDCP, EDID and DDC. Orange LEDs next to each output port indicate whether the splitter is powered on and transmitting a signal to the connected displays. The splitter works with all operating systems and is small enough to carry in your backpack or computer bag. Plug-and-play convenience means no software or drivers are needed. An included USB Micro-B cable connects between the source and the splitter to provide power, so no external power supply is required.

#### **Features**

Converts and Splits Mini DisplayPort Signal to 2 VGA Displays SimultaneouslyIdeal for offices, conference rooms, trade shows and classroomsBuilt-in Mini DisplayPort cable connects to sourceIncluded USB Micro-B cable supplies power to splitterSave money on new Mini DisplayPort displays or docking stations

**Top-Shelf Performance**Supports video resolutions up to 1080p @ 60 Hz (1920 x 1080)Complies with HDCP, EDID and DDCLEDs indicate whether splitter is powered on and transmitting signal to connected displays

Easy to Use Almost AnywhereWorks with all operating systemsPlug and play—no software, drivers or external power supply requiredCompact unit fits easily in backpack or computer bag

# **Specifications**

| OVERVIEW |              |  |
|----------|--------------|--|
| UPC Code | 037332191489 |  |

### **Highlights**

- Supports video resolutions up to 1080p @ 60 Hz (1920 x 1080)
- Included USB Micro-B cable supplies power to unit
- Works with all operating systems
- Compact enough for easy carrying in backpack or laptop bag
- Plug and play—no software or drivers required

## **Package Includes**

- B155-002-VGA 2-Port Mini DisplayPort to VGA Splitter
- USB Micro-B cable, 3 ft.
- · Owner's manual



| Technology                      | DisplayPort; VGA/SVGA            |  |
|---------------------------------|----------------------------------|--|
|                                 |                                  |  |
| VIDEO                           |                                  |  |
| Max Supported Video Resolution  | 1080p @ 60 Hz (1920 x 1080)      |  |
| Max Supported Color Depth       | 24-bit True Color                |  |
| 3D Video Supported              | Yes                              |  |
| AUDIO                           |                                  |  |
| Audio Specification             | 2.0-channel surround sound audio |  |
| POWER                           |                                  |  |
| Power Consumption (Watts)       | 4.1                              |  |
| USER INTERFACE, ALERTS & COI    | NTROLS                           |  |
| LED Indicators                  | (x2) Orange (Monitor Signal)     |  |
| PHYSICAL                        |                                  |  |
| Material of Construction        | Polycarbonate                    |  |
| Color                           | Black                            |  |
| Rackmountable                   | No                               |  |
| Shipping Dimensions (hwd / cm)  | 20.07 x 14.22 x 4.32             |  |
| Shipping Dimensions (hwd / in.) | 7.90 x 5.60 x 1.70               |  |
| Shipping Weight (kg)            | 0.27                             |  |
| Shipping Weight (lbs.)          | 0.60                             |  |
| Unit Dimensions (hwd / in.)     | 3.0 x 2.4 x 1.0                  |  |
| Unit Dimensions (hwd / cm)      | 7.6 x 6.15 x 2.55                |  |
| Unit Dimensions (hwd / mm)      | 61.5 x 76 x 25.5                 |  |
| Unit Packaging Type             | Вох                              |  |
| Unit Weight (lbs.)              | 0.154                            |  |
| Unit Weight (kg)                | 0.07                             |  |
| ENVIRONMENTAL                   |                                  |  |
| Operating Temperature Range     | 14 to 167 F (-10 to 75 C)        |  |
| Storage Temperature Range       | -4 to 176 F (-20 to 80 C)        |  |
| Relative Humidity               | 0% to 85%, Non-Condensing        |  |
| BTUs                            | 14 BTU/Hr                        |  |
| COMMUNICATIONS                  |                                  |  |





| EDID Compatible                     | Yes                                 |  |
|-------------------------------------|-------------------------------------|--|
|                                     |                                     |  |
| CONNECTIONS                         |                                     |  |
| Number of Ports                     | 2                                   |  |
| Side A - Connector 1                | MINI DISPLAYPORT (MALE)             |  |
| Side A - Connector 2                | MICRO-USB B (FEMALE)                |  |
| Side B - Connector 1                | (2) HD15 (FEMALE)                   |  |
| Connector Plating                   | Nickel                              |  |
| Contact Plating                     | Gold                                |  |
|                                     |                                     |  |
| FEATURES & SPECIFICATIONS           |                                     |  |
| Displayport Specification           | 1.2                                 |  |
| HDCP Specification                  | 1.3                                 |  |
| Driver Required                     | No                                  |  |
| MST Support                         | No                                  |  |
|                                     |                                     |  |
| STANDARDS & COMPLIANCE              |                                     |  |
| Product Compliance                  | RoHS; CE (Europe); REACH; FCC (USA) |  |
| WARRANTY                            |                                     |  |
| WARRANTT                            |                                     |  |
| Product Warranty Period (Worldwide) | 3-year limited warranty             |  |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>