

Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

HDMI over Cat5/6 Extender Kit, Transmitter/Receiver for Video/Audio, PoC, Up to 100 ft. (30 m), TAA

MODEL NUMBER: B126-1P1M-U-POC











Transmitter and receiver extend an HDMI signal via Cat5e/6/6a cable to a projector, monitor or TV up to 100 ft. away. Recommended for digital signs, classrooms, churches, offices and retail settings.

Description

The B126-1P1M-U-POC HDMI over Cat5/Cat6 Extender Kit includes a transmitter and a low-profile receiver that work in tandem to extend an HDMI audio/video signal to a projector, monitor or television. The kit is recommended for digital signs, trade shows, classrooms, churches, offices, retail settings and other applications where the source is located farther than conventional cables allow. HDMI cable (see Tripp Lite's P568-Series) connects the audio/video source, such as a Blu-ray™ player, and optional local display to the transmitter's HDMI ports. Cat5e/6/6a cable connects the transmitter to the receiver's RJ45 port (for best results, use 24 AWG solid-wire Cat6 cable, such as Tripp Lite's N202-Series). The receiver plugs directly into the display's HDMI input port. Built-in PoC technology powers the receiver over Cat5e/6/6a cable, so no external power supply on the display side is needed. The B126-1P1M-U-POC can extend a high-definition 1080p (at 60 Hz) signal up to 50-ft. (15.24 m) and a 1080i signal up to 100-ft. (30.5 m) In addition to crystal-clear video, the B126-1P1M-U-POC delivers full, rich audio up to 7.1-channel surround sound (multi-channel or PCM) and supports 3D and HDCP standards. Easy to set up with no software or drivers to install. Complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

Extends a High-Definition HDMI Audio/Video Signal

- Transmitter extends HDMI A/V signal to low-profile receiver
- Recommended for digital signs, trade shows, classrooms, churches, offices, retail settings and other HDMI A/V applications
- Extends a 1080p (@ 60 Hz) signal up to 50-ft. (15.24 m) from source
- Extends a 1080i signal up to 100-ft. (30.5 m) from source
- Supports 7.1-channel surround sound (multi-channel or PCM) audio
- HDCP and 3D compliant

Easy to Set Up and Use

Built-in Power over Cable (PoC) technology powers the receiver

Highlights

- Built-in Power over Cable (PoC) technology powers the receiver
- Supports high-definition video resolutions up to 1080p (@ 60 Hz)
- Supports 7.1-channel surround sound audio
- · HDCP and 3D compliant
- Plug-and-play operation with no software or drivers required

System Requirements

- Source with HDMI and USB ports (if source has no USB port, a USB wall charger can be used)
- · Display with HDMI port

Package Includes

- Transmitter unit
- Receiver unit
- USB Micro-B cable, 1-ft. (0.31 m)
- USB Micro-B cable, 3-ft. (0.91 m)
- Owner's manual



- Transmitter and receiver connect with Cat5e/6/6a cable (for best results, use Tripp Lite's N202-Series)
- Transmitter connects to source and optional local display using HDMI cable, such as Tripp Lite's P568-Series
- LEDs indicate when units are receiving power or an HDMI signal
- Plug-and-play operation with no software or drivers required

TAA-Compliant

• Complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
UPC Code	037332201003
Product Type	Extender Kit
Technology	HDMI; Cat5/5e; Cat6; POC
VIDEO	
Max Supported Video Resolution	1920x1080 (1080p @ 60Hz)
Max 1280 x 720 (720p) Range (ft)	100
Max 1920 x 1080 (1080p) Range (ft)	50
Transmitter Video Input	НДМІ
Transmitter - Number of Video Outputs	1
Transmitter - Local Display Output	НОМІ
Receiver/Transceiver Video Output	НОМІ
Receiver - Number of Video Outputs	1
Range Extension using other Tripp Lite product	175ft @ 1080i 125ft @ 1080p
Recommended Cabling	N202-Series Cat6 Patch Cable
Other Tripp Lite product used to extend range	B126-110
Max Supported Color Depth	24-bit True Color
HDR Support	No
3D Video Supported	Yes
Chroma Sub Sampling	4:4:4
Maximum Signal Range (ft)	100
Maximum Signal Range (m)	30
Maximum Signal Range Details	100 ft @ 1080i50 ft @ 1080p





AUDIO		
Audio Input	HDMI	
Audio Output	HDMI	
Audio Specification	7.1 Channel Surround Sound	
INPUT		
Bus Powered	No	
POWER		
Power Source Type	USB	
Power Source	Transmitter and Receiver (Included)	
Power Over Cable (PoC) Support	Yes	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	TX & RX: Green (Power), Orange (Activity)	
PHYSICAL		
Color	Black	
Number of Displays	1	
Form Factor/Mounting Options	Pigtail	
Rackmountable	No	
Receiver Unit Dimensions (hwd / in.)	1.52 x 0.85 x 0.81	
Receiver Unit Weight (lbs.)	0.03	
Shipping Dimensions (hwd / cm)	4.39 x 19.99 x 14.20	
Shipping Dimensions (hwd / in.)	1.73 x 7.87 x 5.59	
Shipping Weight (kg)	0.20	
Shipping Weight (lbs.)	0.44	
Transmitter Unit Dimensions (hwd / in.)	2.4 x 0.94 x 2.04	
Transmitter Unit Weight (lbs.)	0.1	
Unit Packaging Type	Box	
Housing	Plastic	
ENVIRONMENTAL		
Operating Temperature Range	32 to 104 °F (0 to 40 °C)	
Storage Temperature Range	5 to 122 °F (-15 to 50 °C)	
Relative Humidity	0% to 85%, Non-Condensing	





COMMUNICATIONS		
Signal Range (ft.)	50	
Signal Range (m)	15	
EDID Compatible	Yes	
IR Remote Extension Support	No	
RS-232 Serial Extension Support	No	
Consumer Electronics Control (CEC) Supported	Yes	
USB Extension Support	No	
CONNECTIONS		
Number of Ports		
Side A - Connector 1	2	
Side A - Connector 2	HDMI (MALE)	
	MICRO-USB B (FEMALE)	
Side A - Connector 3 Side B - Connector 1	RJ45 (FEMALE)	
	HDMI (MALE)	
Side B - Connector 2	MICRO-USB B (FEMALE)	
Side B - Connector 3	RJ45 (FEMALE)	
Connector Plating	Gold; Nickel	
FEATURES & SPECIFICATIONS		
HDCP Specification	1.4	
Driver Required	No	
10/100 Ethernet Extension Support	No	
Built-In Equalizer	No	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY		
Product Warranty Period (Worldwide)	1-year limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies